



THE BEST SOLUTION FOR AGRICULTURE

MISTBLOWER ATM 3PCP

TECHNICAL FEATURES:

- HOT GALVANISED FRAME
- POLYETHYLENE TANK
- HAND WASHING TANK
- INTEGRATED SYSTEM CLEANING TANK
- DIAPHRAGM PUMP WITH VALVE
- ELECTRIC PRESSURE REGULATION
- HYDRAULIC AGITATOR
- SUCTION FILTER WITH ANTI-EMPTYING VALVE
- ORIENTATING CHECK NOZZLES
- Ø 500 AIR CONVEYOR
- 2 WHEELS
- ORIENTATING CHECK VALVE NOZZLES
- 2 SPEEDS
- TRANSMISSION WITH NEUTRAL
- CLUTCH
- HYDR. HORIZONTAL MOVEMENT 90°
- HYDR. VERTICAL MOVEMENT 270°
- HYDR. HEAD LIFT CM. 50
- HYDR, RIGHT AND LEFT INCLINATION 15°
- DEFLECTORS
- REAR BUMPER PROTECTION

HORIZONTAL RANGE MT. 45
POWER ABSORPTION 100 HP



www.osellasrl.it

ACCESSORIES ON REQUEST



Ø 100 WIKA PRESSURE GAUGE



HYDR. POWDER MIXER ASSEMBLY ON THE FILTER



TANK RINSING NOZZLE KIT



LIGHTING LED KIT



VHOSE REEL



TURBO SPRAY GUN

Mistblower brought to the third point, suitable for various treatments on maize crops. The height of the gun tube has been designed to ensure homogeneous spraying to defeat the corn borer. Thanks to its powerful dual impeller gun and the implementation of adjustable nozzles on the entire air outlet side obtains a uniform distribution and an exceptional range of 42-46 Mt. Wide possibility of hydraulic movement: 360° rotation adjustment, adjustment in height 50 cm and inclination 15° right/left. The 3PCP ATM Mistblower stands out for the quality of its components, its sturdy frame, and the possibility of configuring it with numerous accessories in full compliance regulations as the safety and protection of the environment. Fan assemblies can be single or double impeller with double speed multipliers and neutral point and centrifugal clutch. Available in the 1200 litre version



1200 Lt.



n° 2



Ø500



116Lt/min



2+N




≥ 100 Cv



L=150cm P=170cm H=330cm



656 Kg.



42/46



Follow Us



OSELLA & C srl
Via Vittoria n°2 26038 Torre de' Picenardi (CR) TEL. +390375-394105
E-mail: info@osellasrl.it website: www.osellasrl.it